

# LD - Badminton

Sport specific information for badminton.

- [Match statuses in badminton](#)
- [Events in badminton](#)
- [Sport specific XML elements and attributes](#)
- [XML configurations for badminton](#)
  - (ID: 29) Badminton set limit
  - (ID: 118) Use match statuses DEFAULTED

## Match statuses in badminton

ID	Match status	Description	Additional information
----	--------------	-------------	------------------------

## Events in badminton

ID	Event	Description	Coverage	extrainfo	player1	player2
40	Yellow card	Used when the yellow card is confirmed.	Hardphone (BC) iScout (BC)		Player who got the card	-
50	Red card	Used when the red card is confirmed.	Hardphone (BC) iScout (BC)		Player who got the card	-
1010	Betstart	Betstart indicates that betting markets can be activated. Betstart is not only a pre match event but is also used during the match.	Hardphone (BC) iScout (BC)		-	-
1011	Betstop	Betstop indicates that all betting markets are closed due to strong possibility of a goal, penalty, red card, or there is any unclear situation on the field. Betstop is also used whenever there is the need to establish direct communication between the scout and the match Supervisor, or in case of call disconnection.	Hardphone (BC) iScout (BC)		-	-
1013	Match status	Sent when the status of the match changes.	Hardphone (BC) iScout (BC)	See table above for match statuses	-	-
1015	Free comment	Used for any kind of additional information during the match. Example: " <i>Match interrupted due to flood light break down</i> ", etc..	Hardphone (BC) iScout (BC)		-	-
1022	Which team serves first	Information about the player who will start to serve.	Hardphone (BC) iScout (BC)	Possible values: <ul style="list-style-type: none"> <li>• 0 = Covered</li> <li>• 1 = Coverage abandoned</li> <li>• 2 = Match will not be covered</li> </ul>	-	-
1024	Match about to start	Sent shortly before serving player takes the first serve.	Hardphone (BC) iScout (BC)		-	-
1031	Ball in play	Used when the service has been taken and the ball is in play.	Hardphone (BC) iScout (BC)		-	-

1044	Deleted event alert	Manual removal of an event.	Hardphone (BC) iScout (BC)	Id of event that was deleted.	-	-
1102	Coverage status	Sent when the coverage status for the match changes	Hardphone (BC)		-	-
1112	Match stop / suspension	Sent when a match needs to be stopped.	Hardphone (BC) iScout (BC)	Possible values: <ul style="list-style-type: none"> <li>• 0 = Not specified</li> <li>• 1 = Weather conditions</li> <li>• 2 = Darkness</li> <li>• 3 = Injury</li> <li>• 4 = Floodlight failure</li> <li>• 5 = Person entering the field</li> <li>• 6 = Crowd control issue</li> <li>• 7 = Water break</li> <li>• 8 = Disciplinary issue</li> <li>• 9 = Gone to TMO</li> <li>• 10 = Replacing ball</li> <li>• 11 = Facility delay</li> <li>• 12 = Tactical time-out</li> <li>• 13 = Drinks</li> </ul>	-	-
1113	Match stop / suspension over	The match resumes after being stopped.	Hardphone (BC) iScout (BC)		-	-
1127	Let	Triggered whenever a play ends without awarding a point due to any unforeseen situation (e.g. serving player servers before receiving player is ready).	Hardphone (BC) iScout (BC),		-	-
1141	Score change	Information about the match score updated point by point.	Hardphone (BC) iScout (BC)	Possible values: <ul style="list-style-type: none"> <li>• 0 = Standard</li> <li>• 1 = Ace</li> <li>• 2 = Service error</li> <li>• 3 = Red card</li> </ul>	-	-
1142	Black card	Black card status is used whenever a player is being disqualified. Common reasons are persistent or flagrant offence.	-		Player who got the card	-

## Sport specific XML elements and attributes

This section explains what elements / attributes one can expect for badminton matches in addition to the standard elements and attributes, and what the meaning of those elements and attributes is.

### Attributes in <match> element

### XML example

```
<match betstatus="BETSTOP" connectionstatus="0" device="1" extrainfo="0" feedtype="full" firstserve="
away" matchid="10115484" matchtime
="2:23:04" numberofsets="3" setlimit="21" stlid="87528" start="1464858600000" tlid="5261571" tlname="
MATSUTOMO M /
TAKAHASHI A" t2id="6862483" t2name="RAHAYU A / SUGIARTO J F">
...
</match>
```

### XML elements and attributes definition

Elements	Attributes		
	Attribute	Description	Possible values
Match	<i>extrainfo</i>	Integer specifying special information for the match.	Integer. Possible values: <ul style="list-style-type: none"><li>• 0 = Default</li><li>• 28 = Best of 3 (first to 15)</li><li>• 30 = Best of 5 (first to 11)</li><li>• 40 = Best of 5 (first to 11, decider at 14-all)</li><li>• 41 = Best of 5 (first to 11, 3 pt challenge</li><li>• at 10-all)</li></ul>
	<i>firstserve</i>	Which player has first serve of match.	
	<i>setlimit</i>	Please note that this attribute needs to be enabled in the XML configuration options.	
	<i>numberofsets</i>	How many sets are being played in the match.	

### Elements in <match> element

#### XML example

```
<match betstatus="BETSTOP" connectionstatus="0" device="1" extrainfo="0" feedtype="full" firstserve="
away" matchid="10115484" matchtime="
2:23:04" numberofsets="3" setlimit="21" stlid="87528" start="1464858600000" tlid="5261571" tlname="
MATSUTOMO M / TAKAHASHI A"
t2id="6862483" t2name="RAHAYU A / SUGIARTO J F">
<status id="100" name="ENDED" start="1464860478511"/>
<score t1="2" t2="0" type="match"/>
<score t1="21" t2="12" type="set1"/>
<score t1="21" t2="14" type="set2"/>
<serve team="home"/>
<black t1="0" t2="0"/>
<red t1="0" t2="0"/>
<yellow t1="0" t2="0"/>
<tournament id="53068" name="Indonesia Open (SS) 2016, Women Doubles"/>
<category id="259" name="International"/>
<sport id="31" name="Badminton"/>
<events/>
</match>
```

### XML elements and attributes definition

Element	Attributes		
	Attribute	Description	Possible values
score	Multiple occurrences possible, each occurrence describes the amount of points for the specified period in the match. This element always gets included in full feed, and in the delta feed for the following events: <ul style="list-style-type: none"> <li>• Badminton full score (1141)</li> </ul>		
	<i>t1</i>	Amount of points home team.	Integer
	<i>t2</i>	Amount of points away team.	Integer
	<i>type</i>	For what period in the match the points were scored.	String. Possible values: <ul style="list-style-type: none"> <li>• match</li> <li>• set1</li> <li>• set2</li> <li>• set3</li> <li>• set4</li> <li>• set5</li> </ul>
serve	This element always gets included, in both the full feed and the delta feed.		
	<i>team</i>	Which team served.	String. Possible values: "home" "away"
black	This element always gets included, in both the full feed and the delta feed.		
	<i>t1</i>	Amount of black cards home team.	Integer
	<i>t2</i>	Amount of black cards away team.	Integer
red	This element always gets included, in both the full feed and the delta feed.		
	<i>t1</i>	Amount of red cards home team.	Integer
	<i>t2</i>	Amount of red cards away team.	Integer
yellow	This element always gets included, in both the full feed and the delta feed.		
	<i>t1</i>	Amount of yellow cards home team.	Integer
	<i>t2</i>	Amount of yellow cards away team.	Integer

#### Attributes in <event> element

##### XML example

```
<match matchid="9577119" ... >
<events>
<event extrainfo="100" id="650847077" info="ENDED" matchscore="2:0" mtime="1:01:08" setnumber="2"
setscore="21:17" side="none"
stime="1465704613813" type="1013"/>
</events>
</match>
```

#### XML attributes definition

Element	Attributes		
	Attribute	Description	Possible values
event	<i>extrainfo</i>	Attribute containing additional information about the event.	Long
	<i>setnumber</i>	The number of the current set in the match.	Integer
	<i>setscore</i>	Score for current set.	String. Format: "[home]:[away]" Example: "5:4"
	<i>matchscore</i>	Score for current match.	String. Format: "[home]:[away]" Example: "1:0"

#### XML configurations for badminton

This section explains what XML configurations one can expect for this sport in addition to the standard XML configurations, and what the meaning of these configurations is.

### **(ID: 29) Badminton set limit**

If this setting is enabled, <match> elements for badminton matches will contain a setlimit attribute.

#### **XML example**

```
<match betstatus="BETSTOP" connectionstatus="0" extrainfo="0" feedtype="full" matchid="7519874"
numberofsets="3" setlimit="21" start="
1435452000000" t1id="1276433" t1name="ARENDS J / PIEK S" t2id="6444419" t2name="LEE C H R / CHAU H W">
<!-- Message truncated -->
</match>
```

### **(ID: 118) Use match statuses DEFAULTED**

Enabling this setting will allow the system to send match statuses DEFAULTED1 and DEFAULTED2 for badminton.

[Back to top](#)