

LD - Volleyball

Sport specific information for volleyball.

- [Match statuses in Volleyball](#)
- [Events in Volleyball](#)
- [Sport specific XML elements and attributes](#)
- [XML configurations](#)
 - (ID: 48) [Deep coverage volleyball](#)
 - (ID: 34) [Include attribute extrainfovolleyball](#)

Match statuses in Volleyball

Id	Match status	Description	Additional information
0	NOT_STARTED	Not started yet	-
8	FIRST_SET	1st set	-
301	FIRST_PAUSE	1st pause	-
9	SECOND_SET	2nd set	-
302	SECOND_PAUSE	2nd pause	-
10	THIRD_SET	3rd set	-
303	THIRD_PAUSE	3rd pause	-
11	FOURTH_SET	4th set	-
304	FOURTH_PAUSE	4th pause	-
12	FIFTH_SET	5th set	-
305	FIFTH_PAUSE	5th pause	-
441	SIXTH_SET	6th set	-
306	SIXTH_PAUSE	6th pause	-
442	SEVENTH_SET	7th set	-
100	ENDED	The match has ended	-
17	GOLDEN_SET	Golden set	-
37	AWAITING_GOLDEN_SET	Waiting for the golden set to begin	-
130	AFTER_GOLDEN_SET	Golden set has ended	-
93	WALKOVER1	The home team won the match by walkover	-
94	WALKOVER2	The away team won the match by walkover	-
95	RETIRED1	The away team won because the home team retired	-
96	RETIRED2	The home team won because the away team retired	-
61	DELAYED	The match start is delayed	-
80	INTERRUPTED	The match has been interrupted	-
90	ABANDONED	The match has been abandoned	This match status is only sent if the corresponding XML configuration is enabled.

Events in Volleyball

ID	Event	Description	Coverage	extrainfo	extrainfovolleyball
1773	First serve golden set	Team that serves first in tiebreak a golden set.	iScout (BC)	-	-

Sport specific XML elements and attributes

This section explains what elements / attributes one can expect for Volleyball matches in addition to the standard elements and attributes, and what the meaning of those elements and attributes is.

Attributes in the <event> element

XML example

```
<match betstatus="BETSTOP" connectionstatus="1" device="5" extrainfo="0" feedtype="full" matchid="
10114593" matchtime="0:00:00"
numberofsets="5" start="1464768000000" t1id="7026026" t1name="TEST 1" t2id="7026025" t2name="TEST 2">
...
</match>
```

XML elements and attributes definition

Element	Attributes		
	Attribute	Description	Possible values
Match	<i>extrainfo</i>	Integer specifying special information for the match.	Integer. Possible values: <ul style="list-style-type: none"> 0 = Default 8 = Best of 3 sets 15 = 21 points set limit 34 = 25 point set limit, tech-timeout on 12 44 = Best of 7 sets 15 point limit
	<i>firstservegoldenset</i>	Which player has first serve in the golden set. Please note that this attribute needs to be enabled in the XML configuration options first.	Integer
	<i>firstservetiebreak</i>	Which player has first serve in the tiebreak.	Integer
	<i>firstserve</i>	Which player has first serve of match.	Integer
	<i>numberofsets</i>	How many sets are being played in the match.	Integer

Elements in <match> element

XML example

```
<match betstatus="BETSTOP" connectionstatus="1" device="5" extrainfo="0" feedtype="full" matchid="
10114593" matchtime="0:00:00"
numberofsets="5" start="1464768000000" t1id="7026026" t1name="TEST 1" t2id="7026025" t2name="TEST 2">
<status id="0" name="NOT_STARTED" start="0"/>
<score t1="0" t2="0" type="match"/>
<score t1="0" t2="0" type="set1"/>
<serve team="home"/>
<tournament id="1" name="Premier League"/>
<category id="1" name="England"/>
<sport id="23" name="Volleyball"/>
<events/>
</match>
```

XML elements and attributes definition

Element	Attributes		
	Attribute	Description	Possible values
score	Multiple occurrences possible, each occurrence describes the amount of points for the specified period in the match. This element always gets included in full feed, and in the delta feed for the following events: Volleyball full score (1046)		
	<i>t1</i>	Amount of points home team.	Integer
	<i>t2</i>	Amount of points away team.	Integer
	<i>type</i>	For what period in the match the points were scored.	String. Possible values: <ul style="list-style-type: none"> • match • set1 • set2 • set3 • set4 • set5 • goldenset • goldensetmatch
serve	This element always gets included, in both the full feed and the delta feed.		
	<i>team</i>	Which team served.	String. Possible values: <ul style="list-style-type: none"> • "home" • "away"

Attributes in the <event> element

XML example

```
<match matchid="9559079" ... >
<events>
<event extrainfo="0" id="650908581" info="24:16 [T1]" matchscore="2:0" mtime="1:32:14" setnumber="3"
setscore="24:16" side="home"
stime="1465716682281" type="1046" />
</events>
</match>
```

XML attributes definition

Element	Attributes		
	Attribute	Description	Possible values
event	<i>extrainfo</i>	Attribute containing additional information about the event.	Integer
	<i>matchscore</i>	Score for current match.	String. Format: "[home]:[away]" Example: "1:0"
	<i>setnumber</i>	The number of the current set in the match.	Integer
	<i>setscore</i>	Score for current set.	String. Format: "[home]:[away]" Example: "5:4"
	<i>extrainfovolleyball</i>	Attribute containing additional information about the event.	String

XML configurations

This section explains what elements / attributes one can expect for volleyball matches in addition to the standard elements and attributes, and what the meaning of those elements and attributes is.

(ID: 48) Deep coverage volleyball

Enabling this setting will add a new attribute `firstservegoldenset` to the `<match>`-element for volleyball matches. This attribute contains information about what team served first in the golden set.

XML example

```
<match betstatus="BETSTOP" connectionstatus="1" feedtype="delta" firstserve="home" firstservegoldenset="home" matchid="1103190216" numberofsets="3">
<!-- Other match info and events truncated -->
</match>
```

(ID: 34) Include attribute extrainfovolleyball

Enabling this configuration will include the attribute "extrainfovolleyball" (values found in the event table above) in the feed.

[Back to top](#)