

# LO - Bet cancellation



If a bettype for a match should be canceled for any reason, a cancelbet message is sent out.

## XML example

```
<BetradarLiveOdds xmlns="http://www.betradar.com/BetradarLiveOdds"
status="cancelbet" timestamp="1199436169018">
<Match active="1" betstatus="stopped" matchid="661373" matchtime="9"
msgnr="46" status="lp">
<Odds active="1" combination="0" freetext="Next goal" id="13792"
specialoddsvalue="2:0" subtype="13" type="ft3w" typeid="6"/>
</Match>
</BetradarLiveOdds>
```

## XML example

```
<BetradarLiveOdds xmlns="http://www.betradar.com/BetradarLiveOdds"
endtime="1199436022222" starttime="1199435902000"
status="cancelbet" timestamp="1199436037753">
<Match active="1" betstatus="started" matchid="661373" matchtime="7"
msgnr="33" status="lp">
<Odds active="1" combination="0" freetext="Next goal" id="13790"
specialoddsvalue="1:0" subtype="13" type="ft3w" typeid="6"/>
</Match>
</BetradarLiveOdds>
```

## XML attributes definition

Element	Attributes		
	Attribute	Description	Possible values
BetradarLiveOdds	status	What kind of information is contained in the message.	String "cancelbet" (in case of a cancelbet message ).
	starttime	Optional attribute. If starttime and endtime are set, only bets accepted in this interval should be canceled.	Timestamp p in UTC
	endtime	Optional attribute. If starttime and endtime are set, only bets accepted in this interval should be canceled.	Timestamp p in UTC
Odds	id	Unique identifier which corresponds to the odds elements in the previously sent out odds change messages. All bets accepted for these odds should be canceled and cashed out with an odd of 1,0 (stakes returned).	Integer

[Back to top](#)