

LO - Livescore change (score/cards)

Information about score changes and given cards are distributed in two different ways. First of all the updates are sent out as they happen during the match. Additionally a full overview gets sent out at the end of the match, containing all the score and card changes.

Note



These messages only indicate that key statistics of the match have changed, and should not be used for resulting purpose as we have dedicated clearbet messages.

Score change

XML example

```
<BetradarLiveOdds xmlns="http://www.betradar.com/BetradarLiveOdds"
status="score" timestamp="1199435937143">
<Match active="1" betstatus="started" matchid="661373" matchtime="5"
msgnr="29" score="1:0" status="lp">
<Score away="0" home="1" id="7966" player="P. Anderson" scoringteam="
home" time="4" type="live" playerid="115622"/>
</Match>
</BetradarLiveOdds>
```

XML attributes definition

Element	Attributes		
	Attribute	Description	Possible values
BetradarLiveOdds	status	What kind of information is contained in the message.	String "score" (for score change messages)
Match	score	Current score in the match	String Format: "[homescore]: [awayscore]" Before the match has started the value will be "-:-"
Score	away	How many points the away team has.	Integer
	home	How many points the home team has.	Integer
	id	The unique identifier for this score change in this match.	Integer
	canceled	Whether the goal is canceled or not	<ul style="list-style-type: none">• True = The goal was canceled• False = The goal was NOT canceled
	player	The name of the player who scored the point.	String If not available the string will be empty
	scoringteam	What team scored the point.	String "home" = home team scored "away" = away team scored
	time	Match time in minutes when the score change happened.	Integer If no time is known this is set to -1
	type	Type of score change	String "live" = Score during the match
	playerid	The id of the player. This attribute needs to be enabled in the XML configuration.	Integer

Card change

XML example

```
<BetradarLiveOdds xmlns="http://www.betradar.com/BetradarLiveOdds"
status="cards" timestamp="1199436094472">
<Match active="1" betstatus="started" matchid="661373" matchtime="8"
msgnr="37" score="1:0" status="1p">
<Card canceled="false" id="7967" player="P. Anderson" team="home" time="
7" type="yellow" playerid="115622"/>
</Match>
</BetradarLiveOdds>
```

XML attributes definition

Element	Attributes		
	Attribute	Description	Possible values
BetradarLiveOdds	status	What kind of information is contained in the message.	String "cards" (for card change messages)
Card	canceled	Whether the card is canceled or not.	String <ul style="list-style-type: none">"true" = the card was canceled"false" = the card was not canceled
	id	The unique identifier for this card in this match.	Integer
	player	The name of the player who received the card.	String If not available the string will be empty
	team	What team received the card.	String <ul style="list-style-type: none">"home" = home team scored"away" = away team scored
	time	Match time in minutes when the score change happened.	Integer If no time is known this is set to -1
	type	Type of card	String Possible values: <ul style="list-style-type: none">yellowyellowredred
	playerid	The id of the player. This attribute needs to be enabled in the XML configuration.	Integer

Note

The same card and the same score can be sent several times; this is used to update information, for example player name or time. Always check the unique id of the score or card when processing them.

Score and card summary

At the end of the match an overview with all the score changes and given cards is sent.

XML example

```
<BetradarLiveOdds xmlns="http://www.betradar.com/BetradarLiveOdds"
status="score" timestamp="1199436663643">
<Match active="1" betstatus="stopped" matchid="661373" msgnr="78" score="
1:2" status="ended">
<Score away="0" home="1" id="7966" player="P. Anderson" scoringteam="
home" time="4" type="score"/>
<Card id="7967" player="P. Anderson" team="home" time="7" type="yellow"/>
<Card id="7965" player="A. Johnsen" team="away" time="4" type="yellow"/>
<Score away="1" home="1" id="7969" player="" scoringteam="away" time="8"
type="score"/>
<Score away="2" home="1" time="90" type="ft"/>
<Score away="2" home="1" id="7971" player="" scoringteam="away" time="
49" type="score"/>
<Score away="1" home="1" time="45" type="ht"/>
<Card id="7970" player="A. Johnsen" team="away" time="46" type="
yellowred"/>
</Match>
</BetradarLiveOdds>
```

XML attributes definition

Element	Attributes		
	At tri b ute	Description	Possible values
BetradarLiveOdds	st at us	What kind of information is contained in the message.	String "score" (for score change overview if match has ended)
Score	ty pe	Type of score. Note that for all values except "score" no id attribute is available, as this is only summarizing the score during different moments of the match.	String Possible values: <ul style="list-style-type: none">• "score" = score change during match• "ht" = score on half time• "ft" = score on full time• "ot" = score after overtime• "pen" = score after penalties The values "ot" and "pen" are only included if the corresponding XML configuration is enabled.

[Back to top](#)