

# LD - Match list

Client systems can request a list of available scout matches for a specific time frame.

**XML example**

```
<matchlist hoursback="6" hoursforward="24" includeavailable="yes" />
```

*XML attributes definition*

Element	Attributes		
	Attribute	Description	Possible values
matchlist	hoursback	The amount of hours ago the timeframe for the request starts.	Integer
	hoursforward	The amount of hours in the future the timeframe for the requests ends.	Integer
	includeavailable	Optional attribute. If this attribute is passed and the value is "yes", the match list reply will also include matches that are not booked yet, but open for booking.	String yes = Include available matches

**Note**  
The maximum timespan one can request matches for is 300 hours. If the timespan is greater than 300 hours it will automatically be adjusted down to 300 hours. If the optional attribute includeavailable="yes" is set, the maximum values of "hoursback" and "hoursforward" are 48 hours and 240 hours respectively.

**Match list reply**

After the client system sends the match list request, a list of matches within the specified timeframe gets sent back.

### XML example

```
<matchlist>
<match booked="1" distance="10" matchid="798175" start="124482240000"
tlid="560764" tlname="BRØNDBY IF II" t2id="560743" t2name
="KØBENHAVNS BK">
<status id="0" name="NOT_STARTED" start="0"/>
<score t1="0" t2="0" type="current"/>
<tournament id="3422" name="2nd Division East"/>
<category id="8" name="Denmark"/>
<sport id="1" name="Soccer"/>
</match>
<match booked="0" coveredfrom="venue" distance="2577" extrainfo="0"
matchid="4973320" stlid="4412" st2id="4393" start="1244966000000
" tlabbr="ARI" tlid="35276" tlname="ARIZONA CARDINALS" t2abbr="ATL"
t2id="33132" t2name="ATLANTA FALCONS">
<status id="0" name="NOT_STARTED" start="0"/>
<score t1="0" t2="0" type="current"/>
<tournament id="47" name="NFL"/>
<category id="43" name="USA"/>
<sport id="16" name="Football"/>
</match>
<match coveragestatusid="0" coveredfrom="venue" device="3" extrainfo="0"
matchid="11361408" stlid="152332" st2id="249567" start="
1495531320000" tlid="1223041" tlname ="DELHI DAREDEVILS" t2id="8511090"
t2name="GUJARAT LIONS">
<status id="502" name="FIRST_INNINGS_AWAY_TEAM" start="1495531234237"/>
<score t1="0" t2="0" type="match"/>
<innings dismissals="0" runs="0" statusid="502" statusname="
FIRST_INNINGS_AWAY_TEAM"/>
<tournament id="7824" name="Premier League"/>
<category id="497" name="India"/>
<sport id="21" name="Cricket"/>
</match>
</matchlist>
```

### XML attributes definition

Element	Attributes		
	Attribute	Description	Possible values
match	booked	Optional attribute indicating whether a match is booked or not. Only added if includeavailable="yes" was added to the match list request.	Integer 1 = Match is booked 0 = Match is not booked yet, but open for booking.

### Match list filtering

To filter by sport id you can send for example:

### XML example

```
<matchlist hoursback="15" hoursforward="10">
  <sport sportid="1" />
  <sport sportid="2" />
</matchlist>
```

You can also specify matches to filter:

#### XML example

```
<matchlist hoursback="15" hoursforward="10">  
  <match matchid="1" />  
  <match matchid="2" />  
</matchlist>
```

[Back to top](#)